

## MAAG 900PEMG

### GENSET

Standby Power	kVA	900
	kW	720
Prime Power	kVA	800
	kW	640
Soundproof canopy [mm]	W x L x H	2200x5550x3434
Open version [mm]	W x L x H	2200x4900x2570
Fuel tank [liter] -base	diesel	2070
Net total weight with canopy*	kg	8 700
Net total weight open version*	kg	6 700
Noise [in canopy design]	dB(A)	71
Control panel		MGD 500L MK2

\* Including lubrication oil and coolant fluid, excluding fuel

#### [Info] Genset characteristics:

Displays:  
Phase currents (A), Phase voltages (V), Line voltages, Integrated frequency and speed display.  
Cooling water temperature, operating hours counter, oil pressure indicator.

#### [Info] AMF Genset control:

Standard voltage-free indications: genset running, high water temperature, low oil pressure, low battery voltage.




#### [Info] Prime power:

**Prime Power** is the maximum power accessible at the variable load for an unlimited number of hours per year in a variable load setting. It is not advisable that the variable load exceed 70% average of the prime power rating during any operational period. If the engine is run-ning at 100% prime power, yearly hours should not exceed 500. Overload situations should be avoided however a 10% overload capability is available for a 1 hour period within a 12 hour cycle of operation.

#### [Info] Standby power:

**Standby Rating** for a standby engine should be sized for a maximum of 70% average load factor and roughly 500 hours per year. Stand-by power ratings should never be applied except in true emergency outage situations. With standby rated generators there is no overload capability built into



### MOTOR

Manufacturer		PERKINS
Model		4006-23TAG3A
Number of cylinders		6 in Line
Cycle		4
Aspiration		Turbocharger - intercooler
Cooling system		Water
Cooling circuit capacity	liter	105
Oil capacity	liter	113,4
Injection		direct
Speed/Frequency	rpm/Hz	1500/50
Fuel consumption	100%	172
	75%	137
	50%	130

### ALTERNATOR

Manufacturer		MAAG
Number of Phase		3
Power factor		cos φ 0,8
Frequency [Hz]		50
Output voltage [VAC]		230 / 400 V
Protection		IP 23
Connection type		Star
Standby power	[kVA]	900
Insulation class		Class H

### OTHER INFO

web: [www.maaggenerator.com](http://www.maaggenerator.com)

#### CERTIFICATE

ISO 9001:2015  
MAAG LOGSOL Kft.  
Központi Iroda: 1125 Budapest, Széchenyi utca 142.  
E-mail: info@maaggenerator.com, logsol@maaggenerator.com  
Tel: +36 (0)1 460 1000  
Fax: +36 (0)1 460 1001  
www.maaggenerator.com

#### CERTIFICATE

ISO 14001:2015  
MAAG LOGSOL Kft.  
Központi Iroda: 1125 Budapest, Széchenyi utca 142.  
E-mail: info@maaggenerator.com, logsol@maaggenerator.com  
Tel: +36 (0)1 460 1000  
Fax: +36 (0)1 460 1001  
www.maaggenerator.com



All of our products are made in Hungary in our own factory. Please kindly be notified that We reserve the right to make changes without the prior consent of the buyer except the standby and prime power which are always guaranteed. Thank you for understanding.  
All pictures shown here are for illustration purpose only.

MSZ EN ISO 14001:2015, MSZ EN ISO 9001:2015

